



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

SAFETY DATA SHEET

Complying with 1907/2006/EEC Regulation of 18 December 2006 ("REACH Regulation) and Regulation (EC) No 1272/2008 (CLP)

SECTION 1 Product and Company Identification

Product

Product Name: Cure and Seal 12.5

Product Description: Finishing aid

Intended Use: curing membrane

Company

Manufacturer: SureCrete Design Products, Inc.

15246 Citrus Country Drive

Dade City, FL 33523

USA

Contact: 352-567-7973 (telephone general)

813-469-1408 (telephone 24 hour emergency)

813-469-1419

info@surecretedesign.com (e-mail)

352-521-0973 (facsimile)

SECTION 2 Hazards Identification

According to EC Directive 2001/59/EC

Most Important Hazards

Physical / Chemical Hazards: R11; Highly flammable

Health Hazards: R20/21: Harmful by inhalation and in contact with skin

R38: Irritating to skin

GHS – Classification

Physical / Chemical Hazards: H226 Flammable liquid and vapor

Health Hazards: H312: harmful in contact with skin

H315: causes skin irritation

H332: harmful if inhaled

SECTION 3 Composition / Information on Ingredients

This material is regulated as a mixture

Ingredient	CAS #	EC#	% (by weight)
Hazardous			
Solvent Naptha (Petroleum), Light Aromatic	64742-95-6	265-199-0	<15%
Tertiary Butyl Acetate	540-88-5	208-760-7	<10%
Dimethyl Carbonate	616-38-6	210-478-4	<80%
Non Hazardous			
Copolymer of styrene and 2-ethylhexylacrylate	25153-46-2	REACH exempted	<15%



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

SECTION 4 First Aid Measures

Eye Contact: Rinse with running water for 15 mins. Hold eyelids apart while irrigating.

Skin Contact: Wash affected area thoroughly with soap and water. Wash clothing before reuse.

Inhalation: Move to fresh air. Administer artificial respiration if not breathing. If breathing is difficult, give oxygen. Get medical attention

Ingestion: Get medical attention immediately. Do not induce vomiting.

SECTION 5 Fire Fighting Measures

Extinguishing Media

Appropriate: Foam, CO₂, Dry chemical, water fog

Inappropriate: Solid streams of water

Special Fire Fighting Procedures: Water may be ineffective in fighting fire. If water is used to cool containers, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus required.

Unusual Fire and Explosion Hazard: Closed containers may explode due to a buildup of pressure when exposed to extreme heat. Do not use direct stream on pool fires as product may reignite on water surface.

Flammability Properties

Flash Point (Method): 23.4°C / 74°F

Flammable Limits (Approximate volume % in air): LEL: 4.2 UEL: 12.9

Autoignition Temperature: >465°C / 869°F

SECTION 6 Accidental Release Measures

Personal precautions: Wear protective clothing. Avoid contact with skin. Avoid breathing vapors. Remove all potential sources of ignition. Evacuate personnel to safe areas. Vapors may accumulate to form explosive concentrations. Vapors may collect in low areas.

Environmental precautions: Prevent entry into waterways or confined areas.

Methods for clean-up: Absorb spill onto sand, vermiculite, or any other inert, non-combustible material. Scoop into containers for later appropriate disposal.

SECTION 7 Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Avoid handling of vapor or mist. Do not permit eating, drinking, smoking near material. Remove all potential sources of ignition.

Storage: Keep containers tightly closed, in dry, cool, well ventilated place. Do not store together with strong oxidizing agents.

SECTION 8 Exposure Control / Personal Protection



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

Exposure limit values: TLV –ACGIH 100 ppm (TWA), 150 ppm (STEL)
OSHA-PEL 100 ppm (TWA)
MAK-GER 440 mg/m³ (TWA)
REL-NIOSH 100 ppm (TWA), 150 ppm (STEL)

Occupational exposure controls: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Respiratory protection: Wear suitable NIOSH approved respirator when ventilation is inadequate

Hand protection: Chemically compatible gloves

Eye protection: Safety glasses with side shields

Skin protection: Minimize skin contact with appropriate long-sleeved clothing

Hygiene measures: Observe good industrial hygienic practices. Frequently launder or discard protective clothing, equipment.

Environmental exposure controls: The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Utilize explosion proof equipment for ventilation.

SECTION 9 Physical and Chemical Properties

General

Physical state: liquid

Color: clear

Odor: characteristic aromatic

Safety Data

pH: not available

Boiling point: ~90°C / 194°F

Flash point: 44°C / 74°F

Flammable limits (approximate volume % in air): LEL: 1.1 UEL: 7.0

Autoignition temperature: >450°C / 842°F

Vapor pressure (mm Hg.): 42 mm/Hg @ 20°C / 68°F

Water solubility: negligible

Vapor density (air = 1): >3.1

Specific gravity (water = 1): 1.06

VOC: 389 g / L

Oxidizing properties: not applicable

Explosive properties: not applicable

Other Information

Freezing Point: 2 - 4°C / 36 - 40°F

Hygroscopic: no

SECTION 10 Stability and Reactivity

Stability: Stable under normal conditions

Conditions to avoid: heat, flame, sparks, other sources of ignition

Materials to avoid: Strong oxidizing agents

Hazardous decomposition products: material does not decompose at ambient temperatures



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

Hazardous polymerization: will not occur**SECTION 11 Toxicological Information****Acute Toxicity**

Route of Exposure	Conclusion / Remarks
<i>Inhalation</i>	
Toxicity : LC50 > 5000 ppm	Minimally toxic based on available literature
Irritation: data available	Elevated temperatures or mechanical action may form vapors, mist, or fumes that may be irritating to the eyes, nose, throat, or lungs based on available literature
<i>Ingestion</i>	
Toxicity: LD50 > 13,000 mg/kg oral rat	Minimally toxic based on available literature
<i>Skin</i>	
Toxicity: LD50 > 4320 mg/kg	Minimally toxic based on available literature
Irritation: data available	Irritating to the skin based on available literature
<i>Eye</i>	
Irritation: data available	Moderately irritating to the eyes based on available literature

Chronic / Other Effects

Vapor concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects. Small amounts of liquid aspirated into the lungs during ingestion or vomiting may cause chemical pneumonitis or pulmonary edema. Very high exposures (confined space or abuse) to light hydrocarbons may result in abnormal heart rhythm. Concurrent high stress levels and / or co-exposure to high levels of hydrocarbons (above occupational exposure limits) and exposure to heart stimulating substances like epinephrine, nasal decongestants, asthma drugs, or cardiovascular drugs may initiate arrhythmias. Studies have revealed carcinogenicity in laboratory animals. The relevancy of these findings to humans is uncertain.

SECTION 12 Ecological Information**Ecotoxicity:** Material expected to be toxic to aquatic organisms**Mobility:** Material highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids**Persistence and degradability***Biodegradation:* expected to be readily biodegradable*Atmospheric oxidation:* expected to degrade rapidly in atmosphere*Bioaccumulation potential:* very low potential to bioaccumulate*Other:* material is VOC**SECTION 13 Disposal Considerations**



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

Methods of disposal: waste must be disposed of in accordance with federal, state, and local environmental control regulations.

Hazardous waste: European waste code 14 06 03. The material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that directive unless Article 1(5) of the Directive applies.

Section 14 Transport Information

International transport regulations

<i>Regulatory Information</i>	<i>UN number</i>	<i>Proper shipping name</i>	<i>Class</i>	<i>Packing group</i>	<i>Additional information</i>	<i>Marine pollutant</i>
ADR/RID class	1263	Paint related material	3	III		NA
IMDG class	1263	Paint related material	3	III	EMS-No: F-E, S-D	No
IATA class	1263	Paint related material	3	III		NA

National Fire Protection Association Hazard Ratings (NFPA)

Health hazard 2

Flammability 3

Stability 0

SECTION 15 Regulatory Information

US FEDERAL

OSHA Hazards: Combustible liquid

TSCA Inventory Listing: listed or exempt

SARA 302 Status: no chemicals to report

SARA 311/312 Classification: "Fire hazard"

SARA 313 Chemical: none to report

CERCLA Hazardous Substance: none

WHIMS: Class B, Division 3: Combustible liquid

EU

Material is dangerous as defined by the EU Dangerous Substances / Preparations Directives

Risk phrases: R10: flammable
R38: irritating to skin
R20/21: harmful by inhalation and contact with skin

Safety advice: S02: keep out of reach of children
S25: Avoid contact with skin

Dangerous as defined by EU CLP 2008:



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

Physical/chemical properties:

Flammable liquids: flam. liquid 3:

H226: flammable liquid and vapor

Health hazards:

Skin corrosion / irritation: skin irrit. 2:

H315: causes skin irritation

Acute toxicity – inhalation: acute tox. Cat. 4:

H332: harmful if inhaled

Acute toxicity – dermal: acute tox. Cat. 4:

H312: harmful in contact with skin

Precautionary statements

P210: keep away from heat, sparks, open flame, hot surfaces / no smoking

P243: take precautionary measures against static discharge.

P261: avoid breathing dust, fumes, gas, mist, vapor, spray

P280: wear protective gloves, clothing, eye and face protection

P303+P361+P353: if on skin / hair: remove / take off immediately all contaminated clothing; rinse with water

INTERNATIONAL REGULATIONS**AICS:** listed**MITI:** listed**DSL / NDSL:** listed**EINECS:** listed**PICCS:** listed**Korean, China Inventory List:** listed**STATE REGULATIONS**

California Prop.65: This product contains trace elements known to the State of California to cause cancer, birth defects, or reproductive harm. California law requires the manufacturer to give the above warning in the absence of definitive testing to prove the defined risks do not exist.

SECTION 16 Other Information**Hazard Ratings**

	<i>health</i>	<i>flammability</i>	<i>reactivity</i>
HMIS	1	2	0
NFPA	1	2	0

Full text of R-phrases referred to in section 2:

R10: flammable

R11: highly flammable

R38: irritating to skin

R20: harmful by inhalation

R20/21: harmful by inhalation and in contact with skin

Full text of hazard statements referred to in section 2:



Product Name: Cure and Seal 12.5

Revision Date 06/18/12

H225: highly flammable liquid and vapor

H226: flammable liquid and vapor

H332: harmful if inhaled

H312: harmful in contact with skin

H315: causes skin irritation

Recommended restriction: for use by trained professionals, having read the complete MSDS

Key Legend:

ACGIH – American Conference of Governmental Industrial Hygienists

HMIS - National Paint and Coating Hazardous Materials Identification System

NFPA – National Fire Protection Agency

OSHA – Occupational Safety and Health Administration

WHIMS – Workplace Hazardous Materials Information System

AICS – Australian Inventory of Chemical Substances

MITI – Japanese Ministry of Trade and Industry Inventory Listing

DSL – Canadian Domestic Substance List

NDSL - Canadian Non-domestic Substance List

EINECS – European Inventory of Existing Commercial Chemical Substances Listing

PICCS – Philippines Inventory List

NTP – National Toxicology Program

IARC – International Agency for Research on Cancer

R – Risk Phrases

S – Safety Phrases

Date of printing 05/08/12

According to Regulation (EC) No. 1907/2006 (REACH), Annex II, Commission Directive 2001/59/EC and REGULATION (EC) No. 1272/2008 (CLP)

To the best of our knowledge the information contained here is accurate. However, neither the above named manufacturer nor any of its distributors assumes any liability whatsoever for the accuracy or the completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.