

## X-treme Terrazzo Material Safety Data Sheet

Se	ctior	<mark>ו 1</mark> :	Product	&	Company	Information
_	-				_	

Product Name: X-treme Terrazzo Manufacturer: SureCrete Design Products

Address: SureCrete Design Products 15246 Citrus Country Drive Dade City, FL 33523

Service Used:Cementitious CompositeApplication:Specialty Aggregate

Emergency Phone: 1-800-544-8488 CHEMTREC: 1-800-424-9300

Section 2: Ingredient Information					
Ingredient / CAS #	OSHA PEL	ACGIH TLV	% by weight		
Portland Type 1 Cements CAS# 65997-15-1	15 mg total dust/ m <sup>3</sup> 5 mg respirable dust/ m <sup>3</sup>	10mg total dust/ m <sup>3</sup>	67 - 95		
Proprietary Ingredients	NA	NA	5 - 26		

Section 3: Physical/ Chemical Characteristics			
Boiling Point: >4,046°F	Specific Gravity (H2O = 1): 2 -3		
Vapor Pressure (mm Hg.): N/A	Melting Point: 3,100 °F		
Vapor Density (Air = 1): N/A	Evaporation Rate: N/A		
Solubility In Water: slightly soluable	Appearance and Odor: White powder w/ no odor		

Section 4: Fire and Explosion Hazard Data					
Flash Point: not	Flammable Limits: not	LEL: N/A	UEL: N/A		
flammable	flammable				
Extinguishing Media: since not flammable, use appropriate media for surrounding materials					
Special Fire Fighting Procedures: Avoid exposure to wet product. May clog waterways as material hardens.					
Unusual Fire and Explosion Hazard: None					

Section 5: Reactivity Data				
Stability: Stable	<b>Conditions To Avoid:</b> Wet environment as product will harden			
Incompatibility (Materials to Avoid): Caution necessary with strong oxidizing agents				
Hazardous Decomposition or Byproducts: none reported				
Hazardous Polymerization: Not known to occur	Conditions To Avoid: None Known			

Section 6: Health Hazard Data					
Route(s) of Entry:	Inhalation	Skin and Eye Contact	Ingestion		
Health Hazards   Acute Inhalation: Exposure to airborne dust may cause irritation to respiratory tract, cough, wheezing.   Skin and Eye Contact: Direct contact with eyes may cause irritation resulting in tearing, stinging and redness.   Prolonged or repeated skin contact may cause irritation or even severe burns that develop after exposure.   Ingestion: May cause burns in esophagus and stomach.   Chronic Bronchitis may develop. Extended and severe exposure may cause silicosis. Some studies have linked autoimmune diseases and kidney diseases to high exposure.					
Carcinogenicity:	NTP - No	IARC Monographs –Yes (for respirable crystalline silica)	OSHA Regulated - No		
Signs and Symptoms of E	xposure: Mainly a mucous m	embrane irritant. Burns may d	levelop.		
Medical Conditions Gener be aggravated by exposure.	ally Aggravated by Exposur	e: Pre-existing respiratory dis	orders or skin diseases may		
	Emergency and Fi	rst Aid Procedures			
<b>Inhalation:</b> Move to fresh air to avoid nuisance symptoms. If irritation persists, consult physician	Skin Contact: Wash affected area thoroughly with soap and water. If irritation persists, consult physician	<b>Eye Contact:</b> Rinse with running water, hold eyelids apart while irrigating on the way to emergency facility. If irritation persists, consult physician	<b>Ingestion:</b> Do not induce vomiting. Drink 4 – 8 ozs. of water to dilute material in stomach. Consult physician		
Section 7: Precautions for Safe Handling and Use Steps to Be Taken if Material is Released or Spilled: Sweep up, place in container and hold for disposal. Wear personal protective clothing and equipment. Minimize creating airborne dust through the use of appropriate vacuuming and wet-mopping. Waste Disposal Method: Dispose of in an approved chemical waste landfill or incinerate in accordance with					
applicable federal, state, and local regulations.   Precautions to Be Taken in Handling and Storage: Normal precautions according to good housekeeping practices should be followed. Store in a dry place and keep sealed until ready for use to prevent caking due to moisture pickup.   Other Precautions: None known					
Section 8: Control Measures					
Respiratory Protection: Use OSHA / NIOSH approved respirator if threshold levels are exceeded					
Ventilation					
Local Exhaust: Preferred	Mechanical (General): Recommended, NEC Class II equipment	Special: None known	<b>Other:</b> Monitoring levels of respirable dust is required to provide appropriate ventilation		
Protective Gloves: Chemical Resistant Gloves Eye Protection: Safety goggles or face shield					
Other Protective Clothing or Equipment: As appropriate to prevent contact with the body					

Work / Hygienic Practices: Normal good housekeeping practice; launder contaminated clothing before reuse.

## Section 9: Transportation / Shipping / Regulatory

Hazard Class: Not regulated

Surface Freight Classification: Not regulated